

Eaton GECMA IS Tablet PC

Intrinsically Safe Tablet PC for Zone 1/21



- **Lightweight design for enhanced portability**
- **Large 10.1-inch display for optimal information visibility**
- **High-capacity battery**
- **Provides excellent connectivity through Wi-Fi, LTE, Bluetooth, and NFC**
- **Front & rear camera or optional without camera**
- **Designed for optimal performance and reliability in harsh and hazardous environments**

The Gecma IS Tablet PC is the latest innovation designed to meet industry demands for durable, resilient mobile devices that seamlessly integrate operational and business data while remaining fully functional in harsh and hazardous environments.

The Gecma IS Tablet PC combines state-of-the-art hardware with a Microsoft Windows operating system to support customers on their digital transformation journey toward Industry 4.0. Engineered from the outset to be the lightest and fastest Windows device in its class, the Gecma IS Tablet PC is certified for ATEX/IECEX Zone 1/21 and UL 913 Class I, II, III, Division 1.

Powered by an Intel® Quad-Core CPU, 8GB RAM, and 256GB storage, the Gecma IS Tablet PC is the ideal solution to support your operational needs. Its 10.1-inch display with a 2560 × 1600 resolution delivers a best-in-class viewing experience for commissioning, maintenance, inspection, asset management, and other critical applications. Even accessing your Distributed Control System (DCS) and Manufacturing Execution System (MES) becomes effortless with such a powerful device.

The integrated lithium-ion battery pack provides a typical operating time of 12 hours before recharging is required. Charging through our docking station takes approximately 2.5 hours to reach 90% and 4 hours for a full charge.

You can safely and securely connect your Gecma IS Tablet PC to your existing Windows IT/OT infrastructure, enabling seamless sharing of mission-critical data across your organization for improved visibility, collaboration, decision-making, and performance. With integrated Wi-Fi, Bluetooth, and NFC, you can leverage your on-site infrastructure and a wide range of accessories to support local applications. For remote locations or integration into proprietary cellular networks, optional LTE connectivity ensures fast and reliable performance.

The Gecma IS Tablet PC conveniently includes two cameras—a front-facing and a rear-facing camera. For security-sensitive applications, we also offer a version of the device without any cameras.

The Gecma IS Tablet PC, running the Microsoft Windows operating system, has successfully passed Eaton cybersecurity tests and supports Intel® TXE Boot Guard 2.0.

SPECIFICATION

Certification UL	UL 913 8th Edition, CSA C22.2 No. 60079-0 & -11 Class I, II, III, Division 1, Groups A-G, T4 Tamb = -20°C...+55°C, IP67
Certification IECEx	IECEX Ex ia IIC T4 Ga Ex ia IIIC T135°C Da Tamb = -20°C...+55°C, IP67
Certification ATEX	ATEX II 2G Ex ia IIC T4 Ga Ex ia IIIC T135°C Da Tamb = -20°C...+55°C, IP67
Exterior	W x H x D: 278 x 207 x 13.8 mm (10.94 x 8.15 x 0.54 in) - without battery W x H x D: 278 x 207 x 28.3 mm (10.94 x 8.15 x 1.11 in) - at battery section Estimated final weight: 1430g (3.08 lbs)
Display	10.1" / 25.6 cm AHVA display WQXGA (2560 x 1600 px) Contrast 1000:1 (min.: 800:1) Brightness 540 NITs Viewing angle (up/down, left/right) 170° 16.7M colors
Battery	7.2VDC 2x 3450mAh Rechargeable Lithium Ion
Charging Time (in standby)	Wall adaptor: 0-90% in 2.5hours, to 100% in approx. 3.5 hours Docking station: 0-90% in 2.5hours, to 100% in approx. 4 hours
CPU, RAM & Storage	Intel® Quad-Core Apollo Lake processor Base: 1.6GHz, Burst 1.8GHz 8GB RAM, 256GB storage MicroSDXC Card Slot (up to 2 TB cards supported)
Wireless & LTE	Wi-Fi 802.11 a/b/g/n/ac/ Bluetooth 5.2 + HS NFC LTE Optional: Worldwide LTE-A Cat 12 and UMTS/ HSPA+
Location	GPS / GLONASS / Galileo (Cold start <30s, Hot start < 2s)
Connections	Magnetic pin connector for rapid charging with wall charger Docking connector supports LAN, USB 2.0, 3.0, USB-C, HDMI, SD Card, and audio jack
Software	Windows 11 IoT
Video & Audio	Main Camera (rear-facing): 8MP Auto-focus with flash Image: 3264 x 2448 px jpg, video: 1080p (Full HD 1920 x 1080) 30 fps Secondary Camera (Front-facing) Image: 1920 x 1080 px jpg, video: 1080p (FullHD 1920x1080) 30 fps 1 digital microphone front facing microphone array. Stereo speakers
Sensors	Ambient light sensor (ALS), Accelerometer, Gyroscope, E-Compass, SAR proximity sensor
Security	Intel® TXE Boot Guard 2.0 FW TPM (Intel® PTT3) Intel® Trusted Execution Engine Interface (Intel® TXEI) Driver Intel AES New Instructions BitLocker
In the Box	1x GECMA Intrinsically Safe Tablet 1x Tablet Charger: 12VDC 3.33A power supply and adaptor



Eaton Electric Limited,
Great Marlings, Butterfield, Luton
Beds, LU2 8DL, UK.
Tel: + 44 (0)1582 723633 Fax: + 44 (0)1582 422283
E-mail: mtlenquiry@eaton.com
www.mtl-inst.com

© 2024 Eaton
All Rights Reserved
Publication No. EPS Eaton GECMA IS Tablet PC V2
July 2024

EUROPE (EMEA):
+44 (0)1582 723633
mtlenquiry@eaton.com

THE AMERICAS:
+1 800 835 7075
mtl-us-info@eaton.com

ASIA-PACIFIC:
+65 6645 9864 / 9865
sales.mtlsing@eaton.com

The given data is only intended as a product description and should not be regarded as a legal warranty of properties or guarantee. In the interest of further technical developments, we reserve the right to make design changes.